

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

1. (Currently Amended) A roadside post comprising:

an elongate body formed of a single sheet of spring steel, said body ~~[[and]]~~ having a longitudinal axis, a transverse axis transverse to said longitudinal axis, a body front face and a body rear face, wherein: said body front and rear faces transversely extending generally parallel to said transverse axis, said body ~~[[is]]~~ being elastically bendable through 90 degrees from an unbent state about ~~[[a]]~~ said transverse axis; and transverse to said longitudinal axis, said front and rear faces transversely extending generally parallel to said transverse axis a surface coating applied to said body front and rear faces and respectively providing an exposed front face and an exposed rear face of said roadside post.

2. (Currently Amended) The roadside post of claim 1 wherein~~[[.]]~~ said body is elastically bendable through 90° from said unbent state about said transverse axis to either side of said longitudinal axis.

3. (Currently Amended) The roadside post of claim 1 wherein said body ~~is formed from sheet spring steel having~~ has a Rockwell hardness of C40 to C47.

4. (Original) The roadside post of claim 3 wherein said spring steel is high carbon steel C1075.

5. (Currently Amended) The roadside post of claim 1 wherein said body has a transverse width of approximately 75 mm to 120 mm.
6. (Currently Amended) The roadside post of claim 1 wherein said sheet of spring steel has a thickness of approximately 0.9 mm to 1.5 mm.
7. (Original) The roadside post of claim 1 wherein said body has a substantially arcuate transverse cross-section.
8. (Currently Amended) The roadside post of claim 7 wherein said arcuate transverse cross-section has a radius of approximately 100 mm to 250 mm.
9. (Original) The roadside post of claim 1 wherein said body has a channel shaped transverse cross-section comprising a central web and two lateral flanges.
10. (Original) The roadside post of claim 9 wherein the angle formed between said web and each said flange is approximately 150° to 175°.
11. (Original) The roadside post of claim 1 wherein said post further comprises a rigid base adapted to be driven into the ground, a first end of said body being fixed to said base.

12. (Original)        The roadside post of claim 11 wherein said base has a tapered end longitudinally distal of the body, said base tapered end being adapted to be driven into the ground.

13. (Original)        The roadside post of claim 1 wherein a first end of said body is adapted to be driven into the ground.

14. (Original)        The roadside post of claim 13 wherein said body first end is tapered.

15. (Original)        The roadside post of claim 1 wherein said body includes a mark indicative of the location of the surface of the ground when said post is driven into the ground to a design depth.

16. (Original)        The roadside post of claim 15 wherein said mark is a hole.

17. (Previously Presented)        A roadside post installation comprising the roadside post of claim 1 in which said post is driven into the ground.

18. (Currently Amended)        The roadside post installation of claim 17 wherein a recess is formed in the ground immediately adjacent said body to allow uninhibited bending of said body, said recess extending across either of said body front face and said body rear face.

19. (Currently Amended) The roadside post installation of claim 18 wherein said recess extends approximately 50 mm to 150 mm from said transverse axis at the surface of the ground.

20. (Currently Amended) The roadside post installation of claim 18 wherein said recess has a depth of approximately 50 mm to 150 mm.

21. (Currently Amended) The roadside post installation of claim 18 wherein two said recesses are formed in the ground, a first said recess extending across said body front face and a second said recess extending across said body rear face.

22. (Currently Amended) The roadside post installation of claim 18, ~~and comprising a roadside post comprising an elongate body formed of sheet spring steel and having a longitudinal axis, a front face and a rear face, wherein:~~

~~said body is elastically bendable through 90 degrees from an unbent state about a transverse axis transverse to said longitudinal axis, said front and rear faces transversely extending generally parallel to said transverse axis, and~~

~~wherein said post further comprises a rigid base adapted to be driven into the ground, a first end of said body being fixed to said base, and the entire said base is located beneath the surface of the ground.~~

23. (Currently Amended) The roadside post installation of claim 22 wherein ~~[[the]]~~ a top of said base is located at a depth of approximately 50 mm to 150 mm beneath the surface of the ground.

24. (Previously Presented) A method of installing the roadside post of claim 1, said method comprising driving said post into the ground.

25. (Currently Amended) The method of claim 24 ~~wherein the method further comprises~~ comprising forming ~~[[a]]~~ at least one recess in the ground immediately adjacent said body to allow uninhibited bending of said body, said at least one recess extending across either of said body front face and said body rear face.

26. (Currently Amended) The method of claim 25 wherein said at least one recess extends approximately 50 mm to 150 mm from said transverse axis at the surface of the ground.

27. (Currently Amended) The method of claim 25 wherein said at least one recess has a depth of approximately 50 mm to 150 mm.

28. (Currently Amended) The method of claim 25 wherein two said recesses are formed in the ground, a first said recess extending across said body front face and a second said recess extending across said body rear face.

29. (New) The roadside post of claim 1 wherein said body is formed with a plurality of longitudinally extending ribs.

30. (New) The roadside post of claim 29 wherein each said rib has an apex separated from the apex of an adjacent said rib by trough, said apexes of each adjacent pair of said ribs being laterally separated by about 5 mm to about 25 mm.

31 (New) The roadside post of claim 30 wherein each said apex protrudes about 0.2 mm to about 0.8 mm from an adjacent said trough.